

MATERIAL SAFETY DATA SHEET

Ferric Alum Indicator ASTM for Chloride

SECTION 1 . Product and Company Identification

Product Name and Synonym: Ferric Alum Indicator ASTM for Chloride

Product Code: 3760

Material Uses:

Manufacturer: Science Stuff
1104 Newport Ave

Austin, TX 78753

(512) 837-6020

Entry Date : 6/4/2013

Print Date: 6/4/2013

24 Hour Emergency Assistance : Chemtrec 800-424-9300
Canutec 613-996-6666

Health:	3
Flammability:	0
Reactivity:	0

Hazard Rating:
Least Slight Moderate High Extreme
0 1 2 3 4
NA=Not Applicable NE=Not Established

SECTION 2 HAZARD IDENTIFICATION

Causes severe irritation and burns. May Be harmful if swallowed. Avoid breathing vapor or dust. Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed.

SECTION 3 MIXTURE COMPONENTS

SARA 313	Component	CAS Number	Percent Comp.	Dimension	Exposure Limits
<input type="checkbox"/>	Ferrous Ammonium Sulfate	CAS# 7783-85-9	5%	W/V	None Established
<input checked="" type="checkbox"/>	Nitric Acid	CAS# 7697-37-2	38%	V/V	OSHA TWA 2 ppm (5mg/mf), STEL 4 ppm (10mg/mf)
<input type="checkbox"/>	Water, Deionized ASTM Type II	CAS# 7732-18-5	Balance	V/V	None Established

SECTION 4 FIRST AID MEASURES

Causes severe irritation and burns. May Be harmful if swallowed. Avoid breathing vapor or dust. Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed.

FIRST AID: CALL A PHYSICIAN. SKIN: In case of contact, immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Thoroughly clean clothing and shoes before reuse.

EYES: Wash eyes with plenty of water for at least 15 minutes, lifting lids occasionally. Seek Medical Aid. INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen

INGESTION: Give several glasses of milk or water. Vomiting may occur spontaneously, but DO NOT INDUCE! Never give anything by mouth to an unconscious person.

Ferric Alum Indicator ASTM for Chloride

SECTION 5 FIRE FIGHTING MEASURES

Fire Extinguisher Type: Any means suitable for extinguishing surrounding fire
Fire / Explosion Hazards: Strong oxidizer. Contact with combustible materials may cause a fire.
Fire Fighting Procedure: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and clothing.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Absorb spill with inert material, then place in a chemical waste container. Neutralize with a weak base.

SECTION 7 HANDLING AND STORAGE

Store in a cool dry place. Do not get in eyes, on skin, on clothing. Store away from oxidizable materials.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection: None required
Ventilation
Local Exhaust
Mechanical
Protective Gloves: Acid resistant gloves as neoprene or nitrile
Eye Protection: Goggles and Face Shield
Other Protective Equipment: Wear protective clothing to prevent skin exposure

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Melting Point:	Information not available	Percent Volatile by Volume:	>50%
Boiling Point:	Information not available	Evaporation Rate	Information not available
Vapor Pressure:	Information not available	Evaporation Standard	
Vapor Density:	Information not available	Auto Ignition Temp	Not applicable
Solubility in Water:	Soluble	Lower Flamm. Limit in Air	Not applicable
Appearance /Odors:	Clear odorless liquid	Upper Flamm. Limit in Air	Not applicable
Flash Point:	Not flammable		
Specific Gravity:	1		

SECTION 10 STABILITY AND REACTIVITY INFORMATION

Stability: Stable
Conditions to Avoid: High temperatures, Light

Ferric Alum Indicator ASTM for Chloride

Materials to Avoid: Oxidizing materials, metals, strong bases

Hazardous Decomposition Products: Nitrogen Oxides

Hazardous polymerization: Will Not Occur

Conditions to Avoid: None known

SECTION 11 Toxicological Information

SECTION 12 Ecological Information

SECTION 13 Disposal Considerations

SECTION 14 Transport Information

DOT Classification: Corrosive Liquid, n.o.s. (Nitric Acid), 8, UN1760, PG II

DOT Regulations may change from time to time. Please consult the most recent D.O.T. regulations.

SECTION 15 Regulatory Information

SECTION 16 Additional Information

Conditions aggravated/target organs: Corrosive! Oxidizer! Poison! Exposure may be fatal. Acute: Severe burns to skin, eyes, respiratory tract, GI tract; deep tissue burns and ulceration; blindness. Chronic: Dermatitis; eye damage or blindness. Target organs: Mucous membranes, respiratory system, eyes, skin; systemic poison.

Flammability

Health

Reactivity

Revisions

NFPA

0.1

The information herein is believed to be accurate and is offered in good faith for the user's consideration and investigation. No warranty either expressed or implied is made for the completeness or accuracy of the information whether originating from the above mentioned company or not. Users of this material should satisfy themselves by independent investigation of current scientific and medical knowledge that the material can be used safely.