

# MATERIAL SAFETY DATA SHEET

Nickel Standard

## SECTION 1 . Product and Company Identification

Product Name and Synonym: Nickel Standard  
Product Code: 6450  
Material Uses:  
Manufacturer: Science Stuff  
1104 Newport Ave  
Austin, TX 78753  
(512) 837-6020  
Entry Date : 6/12/2013  
Print Date: 6/12/2013  
24 Hour Emergency Assistance : Chemtrec 800-424-9300  
Canutec 613-996-6666

Health:	2
Flammability:	0
Reactivity:	0

Hazard Rating:  
Least Slight Moderate High Extreme  
0 1 2 3 4

NA=Not Applicable NE=Not Established

## SECTION 2 HAZARD IDENTIFICATION

May cause irritation and burns. May be harmful if swallowed. Avoid breathing vapor or dust. Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed.

## SECTION 3 MIXTURE COMPONENTS

SARA 313	Component	CAS Number	Percent Comp.	Dimension	Exposure Limits
<input type="checkbox"/>	Nickel Nitrate	CAS# 13478-00-7	~1%	W/W	OSHA TWA 1 mg(Ni)/mf
<input checked="" type="checkbox"/>	Nitric Acid	CAS# 7697-37-2	3 - 3.5%	W/W	OSHA TWA 2 ppm (5mg/mf), STEL 4 ppm (10mg/mf)
<input type="checkbox"/>	Water, Deionized ASTM Type II	CAS# 7732-18-5	Balance	W/W	None Established

## SECTION 4 FIRST AID MEASURES

May cause irritation and burns. May be harmful if swallowed. Avoid breathing vapor or dust. Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed.

FIRST AID: SKIN: Remove contaminated clothing. Wash exposed area with soap and water. if irritation persists, seek medical attention.

EYES: Wash eyes with plenty of water for at least 15 minutes, lifting lids occasionally. Seek Medical Aid. INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen

INGESTION: Give several glasses of milk or water. Vomiting may occur spontaneously, but DO NOT INDUCE! Never give anything by mouth to an unconscious person.

Nickel Standard

**SECTION 5 FIRE FIGHTING MEASURES**

Fire Extinguisher Type: Any means suitable for extinguishing surrounding fire

Fire / Explosion Hazards: Development of hazardous combustion gases or vapors possible in the event of a fire.

Fire Fighting Procedure: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and clothing.

**SECTION 6 ACCIDENTAL RELEASE MEASURES**

Absorb spill with inert material, then place in a chemical waste container. Neutralize with a weak base.

**SECTION 7 HANDLING AND STORAGE**

Store in a cool dry place. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling. Store between 15 and 25°C

**SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Respiratory Protection: None required

Ventilation

Local Exhaust

Mechanical

Protective Gloves: Gloves to prevent skin exposure as rubber or vinyl

Eye Protection: Splash Goggles

Other Protective Equipment: Wear appropriate clothing to prevent skin exposure

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

Melting Point:	~0° C	Percent Volatile by Volume:	>96%
Boiling Point:	~100° C	Evaporation Rate	0.36
Vapor Pressure:	Information not available	Evaporation Standard	Butylacetate =1
Vapor Density:	Information not available	Auto Ignition Temp	Not applicable
Solubility in Water:	Soluble	Lower Flamm. Limit in Air	Not applicable
Appearance /Odors:	Clear green liquid, odorless	Upper Flamm. Limit in Air	Not applicable
Flash Point:	not flammable		
Specific Gravity:	1.014		

**SECTION 10 STABILITY AND REACTIVITY INFORMATION**

Stability: Stable

Conditions to Avoid: None known

Nickel Standard

Materials to Avoid: Reactive with metals, alkalis. Avoid heat  
Hazardous Decomposition Products: Nitrous oxides  
Hazardous polymerization: not expected to occur  
Conditions to Avoid: None known

**SECTION 11 Toxicological Information**

**SECTION 12 Ecological Information**

**SECTION 13 Disposal Considerations**

**SECTION 14 Transport Information**

DOT Classification: UN3264, Corrosive Liquids, Acidic, Inorganic, n.o.s. (contains Nitric Acid), 8, PG III

DOT Regulations may change from time to time. Please consult the most recent D.O.T. regulations.

**SECTION 15 Regulatory Information**

**SECTION 16 Additional Information**

Warning! Corrosive. May be toxic by ingestion. If ingested, do not induce vomiting unless directed to do so by medical personnel. If large quantities of this material are swallowed, call a physician immediately. May be harmful if inhaled or ingested. May cause respiratory tract, eye and skin burns.

Flammability

Health

Reactivity

Revisions

NFPA

0.2

The information herein is believed to be accurate and is offered in good faith for the user's consideration and investigation. No warranty either expressed or implied is made for the completeness or accuracy of the information whether originating from the above mentioned company or not. Users of this material should satisfy themselves by independent investigation of current scientific and medical knowledge that the material can be used safely.