

MATERIAL SAFETY DATA SHEET

Petroleum Ether

SECTION 1 . Product and Company Identification

Product Name and Synonym: Petroleum Ether
Product Code: P1924
Material Uses:
Manufacturer: Science Stuff
1104 Newport Ave
Austin, TX 78753
(512) 837-6020
Entry Date : 6/13/2013
Print Date: 6/13/2013
24 Hour Emergency Assistance : Chemtrec 800-424-9300
Canutec 613-996-6666

Health:	2			
Flammability:	4			
Reactivity:	0			
Hazard Rating:				
Least	Slight	Moderate	High	Extreme
0	1	2	3	4
NA=Not Applicable		NE=Not Established		

SECTION 2 HAZARD IDENTIFICATION

Keep away from heat and ignition sources. Harmful if swallowed. Avoid breathing vapors. Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed.

Physical state: Liquid.
Odor: Gasoline
OSHA/HCS status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Emergency overview:

DANGER!
CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION.
HARMFUL IF INHALED
MAY BE FATAL IF SWALLOWED.
EXTREMELY FLAMMABLE LIQUID AND VAPOR.
VAPOR MAY CAUSE FLASH FIRE.
CAUSES DAMAGE TO THE FOLLOWING ORGANS:
RESPIRATORY TRACT, SKIN, EYES, CENTRAL NERVOUS SYSTEM, LENS OR CORNEA.

Do not ingest.
Avoid contact with skin and clothing.
Avoid breathing vapor or mist.
Keep away from heat, sparks and flame. Keep container closed.
Use only with adequate ventilation. Wash thoroughly after handling.

Routes of entry:
Inhalation. Ingestion.

Potential acute health effects:

Eyes: Irritating to eyes.
Skin: Irritating to skin.
Inhalation: Toxic by inhalation. Irritating to respiratory system.
Ingestion: Very toxic if swallowed.
Carcinogenicity: No known significant effects or critical hazards.
Mutagenicity: No known significant effects or critical hazards.
Teratogenicity/ Reproductive toxicity: No known significant effects or critical hazards.
Medical conditions aggravated by over-exposure:
Repeated skin exposure can produce local skin destruction or dermatitis. Repeated or

Petroleum Ether

prolonged exposure to the substance can produce lung damage. Repeated or prolonged exposure to contact with spray or mist may chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to the substance can produce target organs damage.

SECTION 3 MIXTURE COMPONENTS

SARA 313	Component	CAS Number	Percent Comp.	Dimension	Exposure Limits
<input type="checkbox"/>	Petroleum Ether	CAS# 8032-32-4	100%	V/V	None Established

SECTION 4 FIRST AID MEASURES

Keep away from heat and ignition sources. Harmful if swallowed. Avoid breathing vapors. Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed.

FIRST AID: SKIN: Remove contaminated clothing. Wash exposed area with soap and water. if irritation persists, seek medical attention.

EYES: Wash eyes with plenty of water for at least 15 minutes, lifting lids occasionally. Seek Medical Aid. INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen

INGESTION: If swallowed, induce vomiting immediately after giving two glasses of water. Never give anything by mouth to an unconscious person.

SECTION 5 FIRE FIGHTING MEASURES

Fire Extinguisher Type: Carbon Dioxide, dry chemical powder or appropriate foam, water spray

Fire / Explosion Hazards: Vapor may travel considerable distance to source of ignition and flash back.

Fire Fighting Procedure: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and clothing.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Remove all sources of ignition. use all personal protective equipment. use inert absorbent material and recover for disposal.

Personal precautions: Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment. Do not touch or walk through spilled material.

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Methods for cleaning up: If emergency personal are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), and use a non-sparking or explosion-proof means to transfer material to a sealable, appropriate container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

SECTION 7 HANDLING AND STORAGE

Store in a cool dry well ventilated area. Keep away from heat and flame. Do not get in eyes, on skin, or on clothing.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection: NIOSH/MSHA-approved respirator

Ventilation

Local Exhaust

Petroleum Ether

Mechanical

Protective Gloves: Solvent resistant gloves as neoprene or nitrile

Eye Protection: Splash Goggles

Other Protective Equipment: Wear appropriate clothing to prevent skin exposure

Petroleum Spirits

ACGIH TLV (United States, 1/2006) Notes: 1996 Adoption Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL) See CFR 58(124) : 36338-33351, June 30, 1993, for revised OSHA PEL. Refers to Appendix A -- Carcinogens.

TWA: 1370 mg/m³ 8 hour(s)

TWA: 300 ppm 8 hour(s)

NIOSH REL (United States, 12/2001)

CEIL: 1800 mg/m³ 15 minute(s)

TWA: 350 mg/m³ 8 hour(s)

OSHA PEL 1989 (United States, 3/1989)

STEL: 1800 mg/m³ 15 minute(s)

STEL: 400 ppm 15 minute(s)

TWA: 1350 mg/m³ 8 hour(s)

TWA: 300 ppm 8 hour(s)

Engineering measures: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking, and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protection

Eyes: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Recommended: splash goggles

Skin: Personal protective equipment for the body should be selected based on the task being performed and risks involved and should be approved by a specialist before handling this product.

Body recommended: lab coat

Respiratory: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Recommended: nitrile rubber

Petroleum Ether

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Melting Point:	-40°C	Percent Volatile by Volume:	>99
Boiling Point:	35°C	Evaporation Rate	Information not available
Vapor Pressure:	40 mm Hg	Evaporation Standard	
Vapor Density:	2.5	Auto Ignition Temp	550°F
Solubility in Water:	Negligible	Lower Flamm. Limit in Air	1.1
Appearance /Odors:	Clear, colorless liquid w/gasoline odor	Upper Flamm. Limit in Air	5.9
Flash Point:	-18°C		
Specific Gravity:	0.6		

SECTION 10 STABILITY AND REACTIVITY INFORMATION

Stability:	Stable
Conditions to Avoid:	Avoid contact with heat, sparks, flames, or other sources of ignition.
Materials to Avoid:	Nitrogen Tetroxide, strong oxidants
Hazardous Decomposition Products:	Oxides of carbon
Hazardous polymerization:	Will Not Occur
Conditions to Avoid:	None known

SECTION 11 Toxicological Information

Chronic effects on humans: CARCINOGENIC EFFECTS Classified A3 (Proven for animals) by ACGIH. Classified 2 (Suspected for humans) by European Union
Causes damage to the following organs: upper respiratory tract, skin, central nervous system (CNS), eye, lens and cornea.

Other toxic effects on humans: Extremely hazardous in case of ingestion.
Very hazardous in case of skin contact (irritant), of eye contact (irritant), of inhalation (lung irritant).

Specific effects
Carcinogenic effects: No known significant effects or critical hazards
Mutagenic effects: No known significant effects or critical hazards
Teratogenicity/Reproductive toxicity: No known significant effects or critical hazards

Sensitization
Ingestion: No known significant effects or critical hazards
Inhalation: Irritating to respiratory system.
Eyes: Irritating to eyes.
Skin: Irritating to the skin.

SECTION 12 Ecological Information

Environmental precautions: No known significant effects or critical hazards.

SECTION 13 Disposal Considerations

Petroleum Ether

Waste disposal: the generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-product should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

SECTION 14 Transport Information

DOT Classification: UN1268, Petroleum Distillates, n.o.s.
(Petroleum Ether), 3, PG II

DOT Regulations may change from time to time. Please consult the most recent D.O.T. regulations.

SECTION 15 Regulatory Information

United States

HCS Classification:
Target organ effects
Highly Toxic material
Irritating material
Flammable liquid

U.S. Federal regulations:

United States inventory (TSCA 8b): listed
SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notifications: No products were found.
SARA 302/304/311/312 hazardous chemicals: Petroleum Spirits
SARA 311/312 MSDS distribution- Chemical inventory- hazard identification: Petroleum Spirits
Immediate (acute) health hazard, Delayed (chronic) health hazard
Clean Water Act (CWA) 307: No products were found
Clean Water Act (CWA) 311: No products were found
Clean Air Act (CAA) 112 accidental release prevention: No products were found.
Clean Air Act (CAA) 112 regulated flammable substance: No products were found.
Clean Air Act (CAA) 112 regulated toxic substance: No products were found.

State regulations:
Pennsylvania RTK: Petroleum Spirits
generic environmental hazard
New Jersey: Petroleum Spirits

Canada
WHMIS (Canada) :
Class B-2 : Flammable liquid
Class D-2B: Material causing other toxic effects (Toxic)
CEPA DSL/ CEPA NDSL : CEPA DSL: Petroleum Spirits
This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

SECTION 16 Additional Information

Petroleum Ether

Flammability

Health

Reactivity

Revisions

NFPA

	0.2	
3/10/2011	0	Creation date LS

The information herein is believed to be accurate and is offered in good faith for the user's consideration and investigation. No warranty either expressed or implied is made for the completeness or accuracy of the information whether originating from the above mentioned company or not. Users of this material should satisfy themselves by independent investigation of current scientific and medical knowledge that the material can be used safely.